

MATERIAL SAFETY DATA SHEET

Bastion Stud Adhesive

SECTION 1: IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	Bastion Stud Adhesive
Other Names:	None
Product Codes/Trade Names:	n/a
Recommended Use:	Used to fix plasterboard and fibre cement to timber or steel framing
Applicable In:	Australia
Supplier:	CSR Building Products Limited ABN 55 008 631 356
Address:	Triniti 3, 39 Delhi Road, North Ryde, NSW 2113, Australia
Telephone:	+61 2 9235 8000 (or 1800 807 668 (available in Australia only))
Email Address:	http://www.csr.com.au/Pages/Contact-Us.aspx
Web Site:	www.csr.com.au
Facsimile:	+61 2 9372 5819
Emergency Phone Number:	000 Fire Brigade and Police (available in Australia only)
Poisons Information Centre:	13 11 26 (available in Australia only)

This Material Safety Data Sheet (MSDS) is issued by the Supplier in accordance with National standards and guidelines from the Australian Safety and Compensation Council (ASCC, formerly National Occupational Health and Safety Commission - NOHSC). The information in it must not be altered, deleted or added to. The Supplier will not accept any responsibility for any changes made to its MSDS by any other person or organization. The Supplier will issue a new MSDS when there is a change in product specifications and/or ASCC standards, codes, guidelines, or Regulations.

SECTION 2: HAZARD IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE: Classified as **Hazardous** according to the criteria of the Australian Safety and Compensation Council ASCC (formerly NOHSC) Approved Criteria For Classifying Hazardous Substances [NOHSC:1008] 3rd Edition.

Bastion Stud Adhesive is classified as **Non-Dangerous** Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

Risk Phrases	Safety Phrases
R21/22: Harmful in contact with skin and if swallowed	S24/25: Avoid contact with skin and eyes.
R36: Irritating to eyes.	S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name:	Synonyms:	Proportion:	CAS Number:
Calcium carbonate		<60%	1317-65-3

MSDS Reference: CSR-SDS-159

Date Issued: 15/02/2012

Acrylic emulsion		10-50%	-
Thickeners		<5%	-
Dispersants		<5%	-
White spirits		<2%	8052-41-3
Dye		<1%	-
Biocide		<1%	-
Surfactant		<1%	-
Water		to 100%	7732-18-5

SECTION 4: FIRST AID MEASURES

Swallowed:	Rinse mouth and lips with water. Do not induce vomiting. If symptoms persist, seek medical attention.
Eyes:	Flush thoroughly with flowing water, while holding eyelids open, for 15 minutes to remove all traces. If symptoms such as irritation or redness persist, seek medical attention.
Skin:	Remove heavily contaminated clothing. Wash off skin thoroughly with water. Use a mild soap if available. Seek medical attention for persistent redness, irritation or burning of the skin.
Inhaled:	Remove to fresh air. If symptoms persist, seek medical attention.
Advice to Doctor:	Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

Flammability:	Non-flammable
Suitable extinguishing media:	Use carbon dioxide, foam, dry chemical or water spray to extinguish, as required for fire in surrounding materials.
Hazards from combustion products:	When heated to decomposition it may emit carbon dioxide, acrid smoke and irritating fumes including acrylic monomers.
Special protective precautions and equipment for fire fighters:	As required for fire in surrounding materials.
HAZCHEM Code:	None

SECTION 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedure:	Spill site may be slippery. Wear protective equipment to prevent skin and eye contamination as in Section 8.
Containment Procedure:	Absorb with sand, vermiculite or similar. Do not allow large volumes to enter drains, storm water systems or waterways.
Clean Up Procedure:	Scrape/shovel material into containers for disposal.

SECTION 7: HANDLING AND STORAGE

Handling:	Dusts can be generated during processing, handling, and storage. Wear protective equipment to prevent skin and eye contamination as in Section 8. Manual handling should be in accordance with Manual Handling Regulations
------------------	--

	and Codes.
Storage:	Store in factory packaging in a sealed container in a cool, dry area.
Incompatibilities:	None

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

National Exposure Standards:	National Occupational Exposure Standard (NES), Australian Safety & Compensation Council, ASCC (formerly NOHSC) White spirits: TWA - 790 mg/m ³ Total dust (of any type, or particle size): TWA - 10 mg/m ³
Notes on Exposure Standards:	All occupational exposures to atmospheric contaminants should be kept to as low a level as is workable (practicable) and in all cases to below the National Standard. TWA (Time Weighted Average): the time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.
Biological Limit Values:	No biological limit allocated.
ENGINEERING CONTROLS	
<input type="checkbox"/> Ventilation:	General room ventilation should be adequate, but local mechanical ventilation may be required if dust is generated, particularly in confined spaces. Work areas should be cleaned regularly by damp sweeping or vacuuming.
<input type="checkbox"/> Special Consideration for Repair &/or Maintenance of Contaminated Equipment:	Recommendations on Exposure Control and Personal Protection should be followed.
PERSONAL PROTECTION	
<input type="checkbox"/> Personal Hygiene	Wash work clothes regularly. Wash hands before eating, drinking, using the toilet, or smoking.
<input type="checkbox"/> Skin Protection:	Engineering controls and work practices should aim to minimise direct contact with the product. Wear loose comfortable clothing. Direct skin contact should be avoided by wearing long sleeved shirts and long trousers, a cap or hat, and gloves (e.g. standard duty leather or equivalent AS 2161 or PVC).
<input type="checkbox"/> Eye Protection:	Safety spectacles with side shields or coverall goggles with direct ventilation (AS/NZS 1336) should be worn if a risk of eye contact exists.
<input type="checkbox"/> Respiratory Protection:	Not required under normal circumstances. An approved particulate respirator conforming to Australian Standards AS/NZS 1715 and 1716 should be worn if dust is generated. Respirators should be correctly fitted, maintained in good condition, and kept in clean storage when not in use. Replaceable filters and cartridges should be replaced regularly in accordance with the manufacturers' guidelines and Australian Standards AS/NZS 1715 and 1716. Use only respirators that bear the Australian Standards mark and are fitted and maintained correctly, and kept in clean storage when not in use.
<input type="checkbox"/> Thermal Protection:	None should be needed under normal circumstances.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

MSDS Reference: CSR-SDS-159
Date Issued: 15/02/2012

Appearance:	Viscous pale green paste
Odour:	Mild ammonia odour
pH, at stated concentration:	Not available
Vapour Pressure:	Not determined
Vapour Density:	Not determined
Boiling Point/Range (°C):	Not determined
Freezing/Melting Point (°C):	Not applicable
Solubility in water:	Insoluble
Specific Gravity (H₂O = 1):	1.4 to 1.6
FLAMMABLE MATERIALS	
<input type="checkbox"/> Flash Point:	Not applicable
<input type="checkbox"/> Flash Point Method:	Not applicable
<input type="checkbox"/> Flammable (Explosive) Limit - Upper:	Not applicable
<input type="checkbox"/> Flammable (Explosive) Limit - Lower:	Not applicable
<input type="checkbox"/> Autoignition Temperature:	Not applicable
ADDITIONAL PROPERTIES	
<input type="checkbox"/> % Volatiles:	<2.5%
<input type="checkbox"/> Volatile Organic Compounds Content (VOC): (as specified by the Green Building Council of Australia)	<2.5%

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability:	Stable
Incompatible Materials:	None
Conditions to avoid:	Dust generation
Hazardous Decomposition Products:	Hydrocarbons and carbon oxides
Hazardous Reactions:	None

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicology data: The information shown is based on the toxicity profiles of a number of acrylic emulsions that are similar in composition to the acrylic polymer used in this product.

Acute Data for acrylic polymer emulsion ingredient:

Oral LD50 - rat: > 5000 mg/kg

Dermal LD50 - rabbit: > 5000 mg/kg

Skin irritation - rabbit: practically non-irritating

Eye irritation - rabbit: inconsequential irritation.

Acute Data for White Spirits:

Oral LD50 - rat: > 5000 mg/kg

Health Effects: Acute (short term)

Swallowed:	Unlikely under normal industrial use, but swallowing more than a mouthful may result in nausea and abdominal discomfort.
Eyes:	Splashes or dust from the dried product may irritate the eyes causing watering and redness. Exposure to dust may aggravate pre-existing eye conditions.
Skin:	The dust from this product, particularly in association with heat and sweat, may cause irritation. It may be drying to the skin due to its physical characteristics.
Inhaled:	Dust is mildly irritating to the nose, throat and respiratory tract and may cause coughing and sneezing. Pre-existing upper respiratory and lung diseases including asthma and bronchitis may be aggravated.

Health Effects: Chronic (long term)

Skin:	Repeated heavy contact with the dust may cause drying of the skin and can result in skin rash (dermatitis) typically affecting the hands. Over time this may become chronic and can also become infected.
Inhaled:	Repeated exposure to the dust may result in increased nasal and respiratory secretions and coughing. Inflammation of lining tissue of the respiratory system may follow repeated exposure to high levels of dust with increased risk of bronchitis and pneumonia.

SECTION 12: ECOLOGICAL INFORMATION

Eco-toxicity:	The physical and chemical nature of the product, and toxicological data on ingredients, indicate that this product is a relatively low risk.
Persistence and Degradability:	Product is persistent and would have a low degradability.
Mobility:	A low mobility would be expected in a landfill situation.

SECTION 13: DISPOSAL CONSIDERATIONS

Product can be treated as a common waste for disposal or dumped into a landfill site in accordance with local authority guidelines. Measures should be taken to prevent dust generation during disposal and exposure and personal precautions should be observed (see Section 8 above).

SECTION 14: TRANSPORT INFORMATION

MSDS Reference: CSR-SDS-159

Date Issued: 15/02/2012

Proper Shipping Name:	None allocated
UN number:	None allocated
DG Class:	None allocated
Subsidiary Risk 1:	None allocated
Packaging Group:	None allocated
HAZCHEM code:	None allocated
Marine Pollutant:	No
Special Precautions for User:	None

SECTION 15: REGULATORY INFORMATION

Poisons Schedule:	Not scheduled
--------------------------	---------------

SECTION 16: OTHER INFORMATION

For further information on this product, please contact:

CSR Building Products Limited (ABN 55 008 631 356), Trinita 3, 39 Delhi Road, North Ryde, NSW 2113, Australia

Phone: +61 2 9372 5888 or 1800 807 668 (available in Australia only)

Fax: +61 2 9372 5877

ADDITIONAL INFORMATION

Australian Standards References:

AS/NZS 1336	Recommended Practices for Occupational Eye Protection
AS/NZS 1715	Selection, Use and Maintenance of Respiratory Protective Devices
AS/NZS 1716	Respiratory Protective Devices
AS 2161	Industrial Safety Gloves and Mittens (excluding electrical and medical gloves)

Other References:

NOHSC:2011(2003)	National Code of Practice for the Preparation of Material Safety Data Sheets 2nd Edition, April 2003, National Occupational Health and Safety Commission.
NOHSC:10005(1999)	List Of Designated Hazardous Substances, April 1999, National Occupational Health and Safety Commission, Sydney.
NOHSC:2007(1994)	National Code of Practice for the Control of Workplace Hazardous Substances (Australian States have similar Codes of Practice in each State).
NOHSC: 2012(1994)	National Code of Practice for the Labelling of Workplace Substances, March 1994, Australian Government Publishing Service, Canberra.
NES	National Occupational Exposure Standards for Workplace Atmospheric Contaminants (NES) Australian Safety and Compensation Council, ASCC (formerly NOHSC) 1995 as amended.
ADG Code	Australian Dangerous Goods Code 6 th Edition.

AUTHORISATION

Reason for Issue: New Product- Bastion Stud Adhesive
Authorised by: Renee Bailey
Date of Issue: 15/02/2012

Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of this information.

END OF MSDS