



# CSR MATERIAL SAFETY DATA SHEET

## CEMINTEL RendaLine Preformed Elements

### SECTION 1: IDENTIFICATION OF THE MATERIAL AND SUPPLIER

<b>Product Name:</b>	<b>CEMINTEL RendaLine Preformed Elements</b>
<b>Other Names:</b>	CEMINTEL RENDALINE Reveal, CEMINTEL RENDALINE Corner Profile, CEMINTEL RENDALINE Contemporary Sill, CEMINTEL RENDALINE Traditional Sill Profiles
<b>Product Codes/Trade Names:</b>	n/a
<b>Recommended Use:</b>	Finishing of recessed window and door openings and external corners
<b>Applicable In:</b>	Australia
<b>Supplier:</b>	CSR Building Products Limited ABN 55 008 631 356
<b>Address:</b>	Trinity 3, 39 Delhi Road, North Ryde, NSW 2113, Australia
<b>Telephone:</b>	+61 2 9235 8000 (or 1800 807 668 (available in Australia only))
<b>Email Address:</b>	<a href="http://www.csr.com.au/Common/Contactus.asp">http://www.csr.com.au/Common/Contactus.asp</a>
<b>Web Site:</b>	www.csr.com.au
<b>Facsimile:</b>	+61 2 9372 5819
<b>Emergency Phone Number:</b>	000 Fire Brigade and Police (available in Australia only)
<b>Poisons Information Centre:</b>	13 11 26 (available in Australia only)

This Material Safety Data Sheet (MSDS) is issued by the Supplier in accordance with National standards and guidelines from the Australian Safety and Compensation Council (ASCC, formerly National Occupational Health and Safety Commission - NOHSC). The information in it must not be altered, deleted or added to. The Supplier will not accept any responsibility for any changes made to its MSDS by any other person or organization. The Supplier will issue a new MSDS when there is a change in product specifications and/or ASCC standards, codes, guidelines, or Regulations.

### SECTION 2: HAZARD IDENTIFICATION

**STATEMENT OF HAZARDOUS NATURE:** Classified as **non-Hazardous** as delivered according to the criteria of the Australian Safety and Compensation Council ASCC (formerly NOHSC) Approved Criteria For Classifying Hazardous Substances [NOHSC:1008] 3rd Edition.

**CEMINTEL RENDALINE Preformed Elements** are classified as **Non-Dangerous** Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

The fine dust in/on the supplied product may include respirable crystalline silica. Cutting, breaking, drilling, sawing, grinding and finishing may generate dust which is classified as **Hazardous**. The following Risk and Safety phrases apply to airborne dust of this product:

<b>Risk Phrases</b>	<b>Safety Phrases</b>
<b>R21/22:</b> Harmful in contact with skin and if swallowed	<b>S22:</b> Do not breathe dust
<b>R48/20:</b> Danger of serious damage to health by prolonged exposure through inhalation	<b>S24/25:</b> Avoid contact with skin and eyes
	<b>S36/37/39:</b> Wear suitable protective clothing, gloves and

CSR MSDS Reference: LWS-SDS-010  
Date Issued: 1/09/2010



eye/face protection
---------------------

### SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name:	Synonyms:	Proportion:	CAS Number:
Calcium silicate hydrate	n/a	<60%	1344-95-2
Crystalline silica	Sand, Quartz	20-30%	14808-60-7
Cellulose	Wood pulp	<15%	9004-34-6
Water	n/a	<15%	7732-18-5
Polyurethane foam	n/a	<6%	-
Xylene	n/a	Trace	1330-20-7
Solvent naphtha	n/a	Trace	64742-95-6
Methylene bisphenyl isocyanate	n/a	Trace	101-68-8
Acrylic primer	n/a	0% to trace	-
Colourant	n/a	0% to trace	-

Note: This product does not contain asbestos or asbestiform fragments.

### SECTION 4: FIRST AID MEASURES

The following applies to dust from this product:

<b>Swallowed:</b>	Rinse mouth and lips with water. Do not induce vomiting. If symptoms persist, seek medical attention.
<b>Eyes:</b>	Flush thoroughly with flowing water, while holding eyelids open, for 15 minutes to remove all traces. If symptoms such as irritation or redness persist, seek medical attention.
<b>Skin:</b>	Remove heavily contaminated clothing. Wash off skin thoroughly with water. Use a mild soap if available. Shower if necessary. Seek medical attention for persistent redness, irritation or burning of the skin.
<b>Inhaled:</b>	Remove to fresh air, away from dusty area. If symptoms persist, seek medical attention.
<b>Advice to Doctor:</b>	Treat symptomatically.

### SECTION 5: FIRE FIGHTING MEASURES

<b>Flammability:</b>	Non-flammable
<b>Suitable extinguishing media:</b>	Use carbon dioxide, foam, dry chemical or water spray to extinguish, as required for fire in surrounding materials.
<b>Hazards from combustion products:</b>	None
<b>Special protective precautions and equipment for fire fighters:</b>	None
<b>HAZCHEM Code:</b>	None

### SECTION 6: ACCIDENTAL RELEASE MEASURES

<b>Emergency Procedure:</b>	Recommendations on Exposure Controls / Personal Protection (see Section 8 below) should be followed during spill clean-up if conditions are dusty.
-----------------------------	--

<b>Clean Up Procedure:</b>	Dust is best cleaned up by bagging, wet sweeping and/or vacuuming to avoid making dust airborne. Wetting down before sweeping up dust may be a useful control measure.
----------------------------	--

## SECTION 7: HANDLING AND STORAGE

<b>Handling:</b>	Avoid breathing dust. Respirable dusts can be generated during processing, handling, and storage. Manual handling should be in accordance with Manual Handling Regulations and Codes.
<b>Storage:</b>	This product should be stored in a dry area.
<b>Incompatibilities:</b>	None

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>National Exposure Standards:</b>	<p><b>National Occupational Exposure Standard (NES), Australian Safety &amp; Compensation Council, ASCC (formerly NOHSC)</b></p> <p>Crystalline silica (quartz): TWA - 0.1 mg/m<sup>3</sup> as respirable dust (<math>\leq 7</math> microns particle equivalent aerodynamic diameter)</p> <p>Calcium silicate: TWA - 10 mg/m<sup>3</sup> measured as inspirable dust</p> <p>Cellulose: TWA - 10 mg/m<sup>3</sup> measured as inspirable dust</p> <p>Total dust (of any type, or particle size): TWA - 10 mg/m<sup>3</sup></p>
<b>Notes on Exposure Standards:</b>	<p>All occupational exposures to atmospheric contaminants should be kept to as low a level as is workable (practicable) and in all cases to below the National Standard.</p> <p>TWA (Time Weighted Average): the time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.</p>
<b>Biological Limit Values:</b>	No biological limit allocated.
<b>ENGINEERING CONTROLS</b>	
<input type="checkbox"/> <b>Ventilation:</b>	Keep exposures to dust as low as practicable. Work in the open air and within external openings (such as doors and windows in buildings) generally provides adequate ventilation. Local mechanical ventilation or extraction may be required in areas where dust could escape into the working environment. Local dust extraction and collection may be used, if necessary, to control airborne dust levels. Hand tools should be used for cutting, drilling or sanding. If the use of power tools is necessary, the power tools must be fitted with efficient and well maintained dust extraction devices. If generated dust cannot be avoided, follow personal protection recommendations.
<input type="checkbox"/> <b>Special Consideration for Repair &amp;/or Maintenance of Contaminated Equipment:</b>	Where possible vacuum or wash down all gear, equipment or mobile plant prior to maintenance and repair work. If compressed air cleaning cannot be avoided, recommendations on Exposure Control and Personal Protection should be followed.
<b>PERSONAL PROTECTION</b>	
<input type="checkbox"/> <b>Personal Hygiene</b>	Wash work clothes regularly. Wash hands before eating, drinking, using the toilet, or smoking.

<input type="checkbox"/> <b>Skin Protection:</b>	Wear loose comfortable clothing. Direct skin contact should be avoided by wearing long sleeved shirts and long trousers, a cap or hat, and gloves (standard duty leather or equivalent AS 2161).
<input type="checkbox"/> <b>Eye Protection:</b>	Ventilated non-fogging goggles (dust resistant AS/NZS 1336) should be worn when working in a dusty environment.
<input type="checkbox"/> <b>Respiratory Protection:</b>	None required if engineering and handling controls are adequate. Where engineering and handling controls are not enough to minimise exposure to total dust and to respirable crystalline silica, personal respiratory protection may be required. The type of respiratory protection required depends primarily on the concentration of the respirable crystalline silica dust in the air, and the frequency and length of exposure time. Amount of exertion required during the work, and personal comfort are other considerations in choice of respirator. A suitable P1 or P2 particulate respirator chosen and used in accordance with AS/NZS 1715 and AS/NZS 1716 may be sufficient for many situations, but where high levels of dust are encountered, more efficient cartridge-type or powered respirators or supplied-air helmets or suits may be necessary. Use only respirators that bear the Australian Standards mark and are fitted and maintained correctly, and kept in clean storage when not in use.
<input type="checkbox"/> <b>Thermal Protection:</b>	None should be needed under normal circumstances.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Grey flat sheets, which may have a tinted or primed finish
<b>Odour:</b>	None
<b>pH, at stated concentration:</b>	Not determined
<b>Vapour Pressure:</b>	Not applicable
<b>Vapour Density:</b>	Not applicable
<b>Boiling Point/Range (°C):</b>	Not determined
<b>Freezing/Melting Point (°C):</b>	Not determined
<b>Solubility in water:</b>	Insoluble
<b>Specific Gravity (H<sub>2</sub>O = 1):</b>	1.3 to 1.7
<b>FLAMMABLE MATERIALS</b>	
<input type="checkbox"/> <b>Flash Point:</b>	Not applicable
<input type="checkbox"/> <b>Flash Point Method:</b>	Not applicable
<input type="checkbox"/> <b>Flammable (Explosive) Limit - Upper:</b>	Not applicable
<input type="checkbox"/> <b>Flammable (Explosive) Limit - Lower:</b>	Not applicable
<input type="checkbox"/> <b>Autoignition Temperature:</b>	Not applicable
<b>ADDITIONAL PROPERTIES</b>	
<input type="checkbox"/> <b>Evaporation Rate:</b>	Not applicable
<input type="checkbox"/> <b>% Volatiles:</b>	Traces
<input type="checkbox"/> <b>Volatile Organic Compounds Content (VOC):</b> (as specified by the Green	Traces

Building Council of Australia)

**SECTION 10: STABILITY AND REACTIVITY**

<b>Chemical Stability:</b>	Stable
<b>Incompatible Materials:</b>	None
<b>Conditions to avoid:</b>	Dust generation
<b>Hazardous Decomposition Products:</b>	None
<b>Hazardous Reactions:</b>	None

**SECTION 11: TOXICOLOGICAL INFORMATION**

**Toxicology data:** No direct data available for this or similar products. However, based on known toxicology of similar ingredients, LD50 would be expected to be >5,000mg/kg.

**Health Effects: Acute (short term)**

<b>Swallowed:</b>	Unlikely under normal industrial use, but swallowing the dust from this product may result in abdominal discomfort.
<b>Eyes:</b>	Dust is irritating to the eyes causing watering and redness. Exposure to dust may aggravate pre-existing eye conditions.
<b>Skin:</b>	The dust from this product, particularly in association with heat and sweat, may cause irritation, but it is not absorbed through the skin. It may be mildly irritating and drying to the skin due to its physical characteristics.
<b>Inhaled:</b>	Dust is mildly irritating to the nose, throat and respiratory tract and may cause coughing and sneezing. Pre-existing upper respiratory and lung diseases including asthma and bronchitis may be aggravated.

**Health Effects: Chronic (long term)**

<b>Skin:</b>	Repeated heavy contact with the dust may cause drying of the skin and can result in skin rash (dermatitis) typically affecting the hands. Over time this may become chronic and can also become infected.
<b>Inhaled:</b>	Repeated exposure to the dust may result in increased nasal and respiratory secretions and coughing. Inflammation of lining tissue of the respiratory system may follow repeated exposure to high levels of dust with increased risk of bronchitis and pneumonia.

**Additional Notes**

<b>Long Term Effects:</b>	<p>Long term occupational over-exposure or prolonged breathing-in (or inhalation) of crystalline silica dust at levels above the NES carries the risk of causing serious and irreversible lung disease, including bronchitis, and silicosis (scarring of the lung), including acute and/or accelerated silicosis. It may also increase the risk of other irreversible and serious disorders including scleroderma (a disease affecting the skin, joints, blood vessels and internal organs) and other auto-immune disorders.</p> <p>ASCC/NOHSC has not classified crystalline silica as a carcinogen.</p> <p>Based on limited animal research, it is possible that repeated inhalation of cellulose fibre dust over time may lead to inflammation and scarring of the lung in humans. Measures taken to protect against crystalline silica dust will also be adequate for preventing health effects from</p>
---------------------------	--

	cellulose.
<b>Special Toxic Effects:</b>	Inhalation of dust, including crystalline silica dust, is considered by medical authorities to increase the risk of lung disease due to tobacco smoking.

## SECTION 12: ECOLOGICAL INFORMATION

<b>Eco-toxicity:</b>	The physical and chemical nature of the product, and toxicological data on ingredients, indicate that this product is a relatively low risk.
<b>Persistence and Degradability:</b>	Product is persistent and would have a low degradability.
<b>Mobility:</b>	A low mobility would be expected in a landfill situation.

## SECTION 13: DISPOSAL CONSIDERATIONS

Waste should be placed in containers and disposed of with other construction waste in accordance with local authority guidelines. Measures should be taken to prevent dust generation during disposal, and exposure and personal precautions should be observed (see Section 8).

## SECTION 14: TRANSPORT INFORMATION

<b>Proper Shipping Name:</b>	None allocated
<b>UN number:</b>	None allocated
<b>DG Class:</b>	None allocated
<b>Subsidiary Risk 1:</b>	None allocated
<b>Packaging Group:</b>	None allocated
<b>HAZCHEM code:</b>	None allocated
<b>Marine Pollutant:</b>	No
<b>Special Precautions for User:</b>	None

## SECTION 15: REGULATORY INFORMATION

<b>Poisons Schedule:</b>	Not scheduled
--------------------------	---------------

## SECTION 16: OTHER INFORMATION

**For further information on this product, please contact:**

CSR Building Products Limited (ABN 55 008 631 356), Trinita 3, 39 Delhi Road, North Ryde, NSW 2113, Australia.

**Phone:** +61 2 9372 5888 or 1800 807 668 (available in Australia only)

**Fax:** +61 2 9372 5877

### ADDITIONAL INFORMATION

**Australian Standards References:**

CSR SDS Reference: LWS-SDS-010

Date Issued: 1/09/2010

AS/NZS 1336	Recommended Practices for Occupational Eye Protection
AS/NZS 1715	Selection, Use and Maintenance of Respiratory Protective Devices
AS/NZS 1716	Respiratory Protective Devices
AS 2161	Industrial Safety Gloves and Mittens (excluding electrical and medical gloves)

**Other References:**

NOHSC:2011(2003)	National Code of Practice for the Preparation of Material Safety Data Sheets 2nd Edition, April 2003, National Occupational Health and Safety Commission.
NOHSC:10005(1999)	List Of Designated Hazardous Substances, April 1999, National Occupational Health and Safety Commission, Sydney.
NOHSC:2007(1994)	National Code of Practice for the Control of Workplace Hazardous Substances (Australian States have similar Codes of Practice in each State).
NOHSC: 2012(1994)	National Code of Practice for the Labelling of Workplace Substances, March 1994, Australian Government Publishing Service, Canberra.
NES	National Occupational Exposure Standards for Workplace Atmospheric Contaminants (NES) Australian Safety and Compensation Council, ASCC (formerly NOHSC) 1995 as amended.
ADG Code	Australian Dangerous Goods Code 6 <sup>th</sup> Edition.

**AUTHORISATION**

Reason for Issue: New CSR Address  
 Authorised by: Ben Thompson  
 Date of Issue: 1/09/2010

Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of this information.

END OF MSDS